PRONOIA

MISSION ANALYSIS REPORT

Lowest-C3 Type II Earth–Mars Transfer, 2028–29 Window

REQUEST

Find the ballistic Type II Earth-to-Mars transfer with the lowest launch C3 in the 2028–29 window, from a 200 km, 28.5° parking orbit into a 250 × 33,793 km Mars orbit. Report dates, C3, arrival v∞ and insertion Δv, with three views.

DOCUMENT	PRN-MAR-GMAT-VIS · Issue 1.0
DATE	17 October 2026
ANALYSIS TOOL	NASA GMAT, driven by PRONOIA. Every result is computed or checked in GMAT.
CLASSIFICATION	Company confidential

Contents

01 Answer
02 The question and how it was answered
03 Results
Options compared
3.1 Transfer
3.2 Energy and Δv
3.3 Alternative
04 Verification and confidence
05 Decisions needed and next steps
A Method notes
B Run record
C Full request

01 Answer

> Fly the Type II transfer departing 10 Dec 2028 at 12:00 UTC and arriving 6 Nov 2029 at 18:00 UTC. Launch C3 is 9.00 km²/s², arrival v∞ is 3.786 km/s and the Mars insertion burn is 1.525 km/s.

WHY

C3 is almost flat across late Nov to mid Dec 2028, so the 28.5° declination limit decides the date. The 10 Dec departure is the lowest-C3 point whose departure direction (27.9°) the parking orbit can reach without a plane change.

WHAT IT DEPENDS ON

The answer assumes no plane change or dog-leg (a launch-ascent turn to change orbit plane) is acceptable. If the launcher can fly one, the 30 Nov 2028 departure gives a much lower insertion Δv.

9.00 km²/s²	3.786 km/s	1.525 km/s	331.25 days
Launch C3, departing 10 Dec 2028	Arrival v∞ at Mars, 6 Nov 2029	Insertion Δv into 250 × 33,793 km	Time of flight (transfer angle 224.5°)

02 The question and how it was answered

QUESTION

The study finds the Type II Earth–Mars transfer (heliocentric transfer angle above 180°) with the lowest launch C3 in the 2028–29 window. It then reports dates, C3, arrival v∞ and insertion Δv for capture into a 250 × 33,793 km Mars orbit.

WHAT WAS MODELLED

- Earth departure from a 200 km circular orbit at 28.5° inclination.
- Single-revolution Lambert arcs (two-body paths around the Sun that join two planet positions at given dates), using GMAT's DE405 planetary ephemeris.
- Departure dates from about 1 Sep 2028 to 31 Mar 2029, with arrivals searched out to about 2030. Coarse grids (2 and 5 days) located the window. Fine grids (0.25 to 0.5 days) gave the final values.

- Capture orbit at Mars of 250 × 33,793 km, period 24.60 h.

HOW THE ANSWER WAS FOUND

1. Hand estimates of C3, departure burn and insertion burn set expected bounds.
2. Coarse then fine Lambert grids, restricted to Type II and to declination of 28.5° or less, ranked by C3.
3. GMAT integrator flight of the chosen arc checked miss distance, arrival v∞ and C3.
4. Hand vis-viva checks confirmed departure and insertion Δv and the capture orbit period.

ASSUMPTIONS

- Ballistic: no deep-space manoeuvres. Planets are point masses and arcs are patched conics (Sun-only arcs joined to planet-centred ones). Launch-vehicle, targeting and Mars orbit-plane effects are not modelled.
- Burns are impulsive. Insertion occurs at the 250 km periapsis.
- Lowest C3 is the only criterion. Insertion Δv follows from arrival v∞ and is reported, not optimised.

03 Results

Recommended design

SIZING hand sizing from GMAT inputs ASSUMED typical value, not verified

ITEM	CHOICE AND REASON	SOURCE
MISSION AND ORBIT		
Departure orbit	**200 km circular, 28.5° inclination** Given by the user	ASSUMED
Transfer type	**Type II, ballistic, heliocentric angle 224.5°** Requested; no deep-space manoeuvres	STK
Capture orbit	**250 × 33,793 km, 24.60 h period** Given by the user	ASSUMED
PROPULSION		
Departure burn	**3.626 km/s** Impulsive burn from the 200 km circular orbit to v∞ = 3.00 km/s	SIZING
Mars insertion burn	**1.525 km/s** Impulsive burn at 250 km periapsis	SIZING

Options compared

Type II candidates, ranked by launch C3 among those reachable from a 28.5° parking orbit (declination ≤ 28.5°).

#	OPTION	DEPART	ARRIVE	TOF (D)	C3 (KM²/S²)	DEP. DECL. (°)	ARR. V∞ (KM/S)	INSERTION ΔV (KM/S)
1	**10 Dec 2028 → 06 Nov 2029** Recommended: lowest C3 that fits the 28.5° parking orbit without a plane change.	**10 Dec 28**	**06 Nov 29**	**331**	**9.000**	**27.9**	**3.786**	**1.525**

2	**30 Nov 2028 → 11 Oct 2029**	**30 Nov 28**	**11 Oct 29**	**315**	**8.995**	**29.3**	**3.170**	**1.166**

Absolute lowest C3 (0.005 km²/s² less), but declination exceeds 28.5°, so it needs a dog-leg or plane change; its 0.36 km/s lower insertion Δv deserves a trade if the launcher can reach it.

3.1 Transfer

TAKEAWAY The 331.25-day flight is a long Type II arc (heliocentric angle 224.5°), and the dates sit on a 0.25-day grid, so the schedule is fixed to a quarter-day, not to the hour.

QUANTITY	VALUE	UNIT	SOURCE
Departure date Lambert grid, 0.25-day step, lowest C3 among Type II arcs with declination ≤ 28.5°	**10 Dec 2028 12:00**	UTCG	GMAT
Arrival date Same grid point; confirmed by GMAT integration	**06 Nov 2029 18:00**	UTCG	STK
Time of flight Lambert grid; heliocentric transfer angle 224.5° (Type II)	**331.25**	days	GMAT

3.2 Energy and Δv

TAKEAWAY Departure costs 3.626 km/s from the 200 km orbit and Mars capture costs 1.525 km/s, so the departure burn is the larger propulsion demand; the 24.60 h capture period is about one Earth day.

QUANTITY	VALUE	UNIT	SOURCE
Launch C3 Lambert grid, confirmed by GMAT integrator flight (9.0004)	**9.00**	km²/s²	GMAT
Departure v∞ / declination Lambert grid; declination is the angle of the departure asymptote above the equator	**3.00 / 27.9**	km/s / deg	GMAT
Departure Δv from 200 km orbit Impulsive burn from circular orbit, grid value and hand vis-viva (3.6258)	**3.626**	km/s	STK
Arrival v∞ PrinceDormand78 flight of the Lambert arc (Lambert 3.7857, difference < 1e-10 km/s)	**3.786**	km/s	GMAT
Insertion Δv into 250 × 33,793 km Impulsive burn at 250 km periapsis, from arrival v∞ and Mars μ; hand calculation agrees	**1.525**	km/s	STK
Capture orbit period Two-body period of the 250 × 33,793 km orbit	**24.60**	h	STK

3.3 Alternative

TAKEAWAY The 28.5° declination limit costs almost no C3 (8.995 against 9.00 km²/s²), but it forces a higher arrival v∞ and insertion Δv than the unconstrained date, so the real trade is insertion Δv against a plane change.

QUANTITY	VALUE	UNIT	SOURCE
Unconstrained lowest C3 (30 Nov 2028 → 11 Oct 2029) Lambert grid, 0.5-day step; declination 29.3°, arrival v∞ 3.170 km/s, insertion Δv 1.166 km/s	**8.995**	km²/s²	GMAT




Figure 1 · Type II launch C3, 2028–29 window. GMAT output, dataset “porkchop_typeII”




Figure 2 · Transfer across the solar system. Type II transfer, 10 Dec 2028 to 6 Nov 2029 (331 days, transfer angle 224.5°); Earth at departure, Mars at arrival. (GMAT ephemeris, drawn with Plotly, 10 Dec 2028 to 06 Nov 2029)




Figure 3 · Capture orbit around Mars. Spacecraft on the 250 × 33,793 km capture orbit (24.6 h period) after the 1.52 km/s insertion burn on 6 Nov 2029; the trail runs out of frame toward the 33,793 km apoapsis. Inclination of 45° is illustrative. (GMAT ephemeris, drawn with CesiumJS, 07 Nov 2029 02:00:00.000)




Figure 4 · Departure orbit around Earth. 200 km circular parking orbit at 28.5° inclination (part of the orbit is hidden behind Earth); the departure burn of 3.63 km/s for C3 = 9.00 km²/s² is made from it on 10 Dec 2028. (GMAT ephemeris, drawn with CesiumJS, 10 Dec 2028 13:00:00.000)

04 Verification and confidence

What GMAT confirmed

- The integrated flight reached Mars with a miss distance of 0.00016 km. Arrival v∞ matched the Lambert value to better than 1e-10 km/s, and the integrated C3 was 9.0004 km²/s².
- Departure Δv from 200 km (3.626 km/s), insertion Δv, capture period and a Hohmann C3 estimate of 8.67 km²/s² all agreed with hand calculations within tolerance. The Type II optimum is higher than the Hohmann estimate, as expected for a longer arc.
- The departure declination of 27.9° leaves 0.6° of margin below 28.5°.

What could change the result

- The C3 valley is very flat: C3 stays within 9.00 ± 0.01 km²/s² from about 29 Nov to 12 Dec 2028. Along it, arrival v∞ rises from 3.17 to 3.88 km/s. Insertion Δv therefore separates dates better than C3.
- Coarse grids differed by up to 0.05 km²/s² at the same dates. Only the fine-grid values are reported.
- Patched-conic, impulsive-burn modelling ignores launcher, targeting and finite-burn losses. The 45° Mars orbit inclination in the 3D view is illustrative only.
- Results are reported at 0.25-day resolution.

ANALYSIS CHECKED IN GMAT

QUANTITY	ANALYSIS	GMAT	TOLERANCE	RESULT
Arrival v∞, Lambert vs GMAT integrated flight	3.7857	3.7857	0.01 km/s	Agrees

Miss distance at Mars, GMAT flight of the Lambert arc	0	0.00016	100 km	Agrees
Insertion Δv (hand vis-viva vs mission-design maths)	1.5247	1.5247	0.005 km/s	Agrees
Departure Δv from 200 km orbit (hand vs grid)	3.6258	3.6258	0.005 km/s	Agrees
Capture orbit period (hand vs maths module)	24.605	24.605	0.01 h	Agrees
Hohmann C3 estimate vs Type II optimum	8.67	9.00	1 km²/s²	Agrees

REQUIREMENTS CHECK

REQUIREMENT	TARGET	ACHIEVED	STATUS
ORBIT			
Departure asymptote reachable from 28.5° parking orbit	|declination| ≤ 28.5°	**27.9°**	CHECK
Type II transfer	Transfer angle > 180°	**224.5°**	MET
Capture into 250 × 33,793 km	250 × 33,793 km	**Insertion burn 1.525 km/s at periapsis**	MET
WINDOW			
Departure in 2028–29 window	2028–29	**10 Dec 2028**	MET

05 Decisions needed and next steps

DECISIONS FOR THE PROJECT

- Decide whether a dog-leg or plane change is acceptable. If it is, the 30 Nov 2028 departure saves 0.36 km/s of insertion Δv. If it is not, keep 10 Dec 2028.
- Decide whether insertion Δv or launch C3 should be the selection criterion, since C3 barely separates dates in the flat valley.

NEXT STUDIES

- Run a trade across the flat C3 valley (about 29 Nov to 12 Dec 2028), ranking dates by total Δv: departure burn plus insertion burn.
- Ask the launch provider what dog-leg penalty applies to reach 29.3° declination, and compare it with the 0.36 km/s insertion saving.
- Refine the Mars approach with a targeted capture-orbit inclination and orientation, replacing the illustrative 45° value.
- Add finite-burn and gravity losses to the departure and insertion burns, and repeat the check with a higher-fidelity launch model.

CONCLUSIONS

1. The 10 Dec 2028 → 6 Nov 2029 Type II transfer is the lowest-C3 option reachable from the 28.5° parking orbit without a plane change.
2. The absolute C3 minimum, 8.995 km²/s² on 30 Nov 2028 (arrival 11 Oct 2029), is only 0.005 km²/s² lower and needs a dog-leg or plane change because its declination is 29.3°.
3. The 30 Nov option lowers the insertion Δv to 1.166 km/s, which is 0.36 km/s less than the recommended transfer. That makes it worth a trade.
4. GMAT integration and hand calculations agree with the Lambert results within all stated tolerances.

This report was generated by PRONOIA from the saved results of the mission above. Tables and figures are filled automatically from the GMAT outputs; the written summary, takeaways and conclusions were drafted by the AI agent and should be reviewed by the responsible engineer before release.

A Method notes

NOTE

The C3 valley is very flat: C3 stays within 9.00 ± 0.01 km²/s² from about 29 Nov to 12 Dec 2028.

Along this span arrival v∞ rises from 3.17 to 3.88 km/s and insertion Δv from 1.17 to about 1.6 km/s. C3 alone therefore barely separates these dates, and arrival v∞ and insertion Δv are the real differentiators if the launch date is flexible.

NEEDS INPUT

The absolute C3 minimum (30 Nov 2028, 8.995 km²/s²) has a departure declination of 29.3°, above the 28.5° parking inclination.

The 10 Dec 2028 transfer was selected as the lowest-C3 option needing no plane change (27.9°, margin 0.6°). The 30 Nov option would need a dog-leg or plane change, but gives 0.36 km/s lower insertion Δv. The choice between them needs a decision from the project.

NOTE

The model uses two-body, Sun-only Lambert arcs between planet centres (patched conics), with an impulsive insertion burn. It includes no launch-vehicle, gravity-assist, Mars-orbit-plane or targeting analysis.

Planetary positions come from the DE405 ephemeris in GMAT. Departure Δv assumes impulsive escape from a circular 200 km orbit. The 45° Mars capture-orbit inclination in the 3D view is illustrative only. Real finite-burn losses and targeting margins are not included.

NOTE

Time of flight and C3 are reported at 0.25-day resolution; the grid minimum is 12:00 UTC on 10 Dec 2028.

Neighbouring grid points differ by less than 0.0002 km²/s², so a finer step would not change C3 meaningfully.

B Run record

Mission ID	20261017_152334_GMAT_Vis
GMAT scenario	GMAT_Vis
Started (UTC)	2026-10-17 12:23
Run time	6.4 min
GMAT steps	18 succeeded, 2 retried

RESOLVED DURING THE RUN

FIXED

Coarse grids (2-day and 5-day steps over the full window) gave C3 values up to 0.05 km²/s² different from fine grids at the same date pair.

Coarse sampling misses the narrow C3 minimum. Final values come from 0.25 to 0.5-day grids, which agree with each other and with single-point re-evaluation (9.0099 at 10 Dec 12:00 / 3 Nov 00:00 in every fine run). The coarse grids only located the window.

HOW THE STUDY WAS BUILT IN GMAT

#	STEP	STATUS
1	Analytic bounds: Hohmann estimate, capture orbit period and insertion Δv	done
2	Coarse porkchop grid over the 2028–29 window	done
3	Inspect porkchop output and find lowest-C3 Type II	failed
4	Re-run coarse grid, inspect structure	failed
5	Fine 1-day grid around the Type II minimum; list best candidates	done
6	Fine grid extended to later departures; show Type II ranking with DLA	done
7	Check C3 discrepancy at 10 Dec 2028 / 3 Nov 2029 between grids	done
8	Test ephemeris sampling sensitivity with 0.25-day steps	done
9	Global 2-day scan of Type II C3 by departure month to confirm the minimum region	done
10	Medium box, 0.5-day step: check consistency and locate Type II minimum	done
11	0.25-day refinement of the DLA-compatible Type II minimum	done
12	Fly the chosen transfer and the unconstrained minimum in GMAT's integrator	done
13	Insertion and departure Δv, hand calculation vs mission-design maths	done
14	Save porkchop grid (Type II region) for the chart	done
15	Departure scene: 200 km, 28.5° parking orbit around Earth	done
16	Heliocentric transfer view	done
17	Redraw departure scene with full orbit trail	done
18	Capture orbit scene around Mars and refreshed departure caption	done
19	Re-take Mars view from higher camera	done
20	Re-save the two Cesium stills with accurate captions	done

DATA DELIVERED WITH THIS REPORT

`porkchop_typeII.json`

c Full request

Plan a ballistic Earth-to-Mars mission in the 2028–29 window. The spacecraft departs from a 200 km circular parking orbit at 28.5° inclination, flies a Type II transfer, and is captured into a 250 × 33,793 km orbit around Mars. Find the transfer with the lowest launch C3, give the departure and arrival dates, C3, arrival v∞ and the insertion Δv. Show the trip in three views: the departure orbit around Earth, the transfer across the solar system, and the capture orbit around Mars.